



Semiautomatic tyre changer with sideways moving arm

Semiautomatic tyre changer with sideways moving arm, suitable for car and motorcycle wheels having rim size from 10" to 20" (max. diameter 1000mm/39", max. wheel width 320 mm/12,5quot;).

Main Features



Car

Suitable for car wheels



Semiautomatic

Model with 3 control pedals, fixed vertical tower, swinging horizontal arm and operating arm with manual lowering and locking by hand-lever.



10"-20"

Allows to operate with tyre assemblies from 10" to 20".



Jaw Clamping

Rim clamping is performed by means of 4 jaws facing each other, driven by pneumatic cylinders connected to the control pedal.



Blade Bead Breaking

Bead breaking by conventional blade, works with tyre assembly in vertical position

Giuliano Industrial S.p.A.



Description

Semiautomatic tyre changer with sideways moving arm, suitable for car and motorcycle wheels having rim size from 10" to 20" (max. diameter 1000mm/39", max. wheel width 320 mm/12,5quot;).

Features

- Fixed vertical arm;
- Sideways moving horizontal arm;
- Operating arm locking system by handwheel;
- 17,5" square turntable, outside clamping;
- Air operated bead-breaker;
- Motor 230/400V-3ph-50Hz.

Standard Features

Rim clamping range	10" - 20"
Max. tyre diameter	1000 mm (39")
Max. tyre width	320 mm (12½")
Max. bead-breaker cylinder force	24700 N
Operating pressure	10 bar (145 psi)
Power supply	230/400 V 3ph
Motor power	0,55 kW
Max. spindle torque	1200 Nm
Inflating pressure limiting device max.	3,5 bar (50 psi)
Net weight	175 kg







Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.